

Powered by



16.5kVA ED16.5LYE/3

*Image may vary from actual model.

The Generating Set Includes a 240V AC Mains Battery Charger

The complete generating set is mounted as a whole onto a heavy duty fabricated steel baseframe.

Anti-vibration pads are fixed between the engine and alternator feet, and the baseframe, ensuring complete vibration isolation of the rotating assembly.

Stringent factory tests are carried out on the generating set, with a full load test completed prior to despatch.

All protective devices, control functions and site load conditions are simulated. The generator and its systems are thoroughly checked prior to leaving our factory.

Warranty on the genset is for 12 months or 1000 hours from date of supply (whichever occurs first) and covers against faulty workmanship, materials and design.

Engine

Lister Petter continues to set the standard in innovation, quality and reliability to meet your requirements for rated performance and efficient operation. Known worldwide for their clean, reliable and long lasting diesel engines, with a range of air cooled or radiator cooled, direct or indirect injection, naturally aspired or turbocharged, there is a specification to suit almost any application. The engines are fitted with a highly efficient noisereducing silencer and governed to a fixed speed of 1500rpm.

Alternator

Crossley SLG Series Alternators are single bearing, 4-pole, with a brushless, rotating field design and are self-excited with power derived from main output windings using the Automatic Voltage Regulator (AVR).

Manufactured using the highest quality copper and steel with all laminations impregnated with epoxy resins, the SLG Series are of a modern design with a precision AVR that allows overloads of 10% for one hour in 12, and overloads for motor starting and short circuit protection of up to 300%.

Available in either Single Phase (240V), 2-Phase (480V) or 3-Phase (415V).

Control System

The control starting system is fitted standard.

Starting is remote or local to the machine with push Start/ Stop button and includes the following digital indicators:

- Oil Pressure
- Engine Temperature
- Frequency
- Volts and Amps
- Emergency stop button
- Output circuit breaker
- Shut Down for low oil & temperature

The control system can also be configured to operate with an Automatic Transfer Switch with logic.

Technical Specifications

16.5kVA

ED16.5LYE/3

1300 656 276
www.wellcross.com.au

Engine Specifications

Engine Model	Lister Petter LPWX4
Engine Speed	1500 rpm
Cylinders	4
Cubic Capacity	1.86 L
Bore/Stroke	86 x 80 mm
Compression Ratio	18.5 : 1
Aspiration	Natural
Starter Voltage	12 V
Flywheel (Max. Continuous Power)	13.6 kW
Combustion Air Flow	1.1 m ³ /min
Cooling Air flow	38 m ³ /min
Cooling System	Radiator Cooled
Heat Rejection to Cooling System	13 kW
Exhaust Gas Flow	2.1 m ³ /min
Exhaust Gas Temperature	550 °C
Fuel Type	Diesel
Fuel Tank Capacity	90 L
Fuel Consumption (Continuous)	3.8 L/h
Fuel Consumption (Standby)	2.85 L/h

Note: Standby reference conditions 27°C (80°F) air inlet temperature 152.4 m (500ft) ASL. All engine performance data based on the above mentioned maximum continuous ratings. Fuel consumption data at full load with diesel fuel with a specific gravity of 0.85 and conforming to BS29869:1988, Class A2.

Design Features

- Heavy duty fabricated steel baseframe
- Bunded Fuel Tank (AS1940-2004 compliant)
- Battery Charger
- Control Panel with Emergency Stop button
- Prime or Standby Power
- Weather protected acoustic canopy

Generator Specifications

Dimensions (L x W x H)	1600 x 850 x 1200 mm
Weight	430 kg

Alternator Specifications

Alternator Model	Crossley SLG
Single Phase	Three Phase
Active Power	16.5 kVA at 0.8 pf (Standby)
Power	12.8 kW
Electric Potential	415 V
Frequency	50 Hz

These ratings are applicable for supplying continuous electrical power at variable load in the event of a utility power failure. No overload is permitted on these ratings.

Canopy

A weather protective acoustic enclosure is included, to protect and prolong the life of your generator. Finished using a powdercoat paint finish, this acoustic canopy reduces the noise level of the generating set to approximately 73 dB(A) at 1 metre from the machine (67 dB(A) @ 7 m).

The Diesel Generator Experts

Welling & Crossley is Australia's largest diesel generator and engine specialist. Australian owned and operated since 1926, Welling & Crossley is an internationally recognised Australian leader in the manufacture and supply of diesel generating sets for industrial or commercial applications. Also available is a complete range of portable generators, inverter generators, back up generators, diesel engines and fire products.

We have the expertise to provide sound advice on your power generating needs. Whether your requirements are prime (continuous) power or standby power applications, you can choose from our standard build sets, or we can tailor to suit your application requirements.