

W&C

DIESEL GENERATORS

LLD7.6/3

kVA@0.8pf (Standby)	7.6
kW	6.08
Volts	415
Frequency	50Hz

These ratings are applicable for supplying continuous electrical power at variable load in the event of a utility power failure.

No overload is permitted on these ratings.



TECHNICAL DATA

Engine model	LPW2 Lister Petter
Alternator model	Crossley SLG Series
Engine speed	1500rpm
Cylinders	2
Cubic capacity	0.93L
Bore/Stoke	86x80mm
Compression ratio	18.5:1
Aspiration	Natural
Flywheel (max. continuous power)	6.8kW
Fuel tank capacity	90L
Fuel consumption (1hr continuous)	1.9L/hr
Fuel consumption (1hr standby)	2.1L/hr
Heat rejection to cooling system	6kW
Exhaust temperature	533 C
Cooling air flow	25m ³ /min
Combustion air flow	0.8m ³ /min
Exhaust gas flow	1.7m ³ /min
Dimensions (LxWxH)	1400x760x1200mm
Weight:	310kg

CONTACT DETAILS

Victoria

59-67 Export Drive
Brooklyn 3012
T: 03 9316 9700
F: 03 9314 0909
Email: sales@wellcross.com.au

New South Wales

U2/1040 Canley Vale Road
Wetherill Park 2164
T: 02 9756 3092
F: 02 9756 3094
E: nsw@wellcross.com.au

Queensland

U2/55 Christensen Rd
Stapylton, 4207
T: 07 3386 2400
F: 07 3386 1241
E: qld@wellcross.com.au

Western Australia

U8/235 Camboon Road
Malaga 6090
T: 08 9248 2955
F: 08 9248 2933
E: wa@wellcross.com.au

Note: Standard reference conditions 27 C (80 F) Air Inlet Temp, 152.4m (500ft) ASL. All engine performance data based on the above mentioned maximum continuous ratings. Fuel consumption data at full load with diesel fuel with a specific gravity of 0.85 and conforming to BS2869:1988, Class A2. Generating set picture may include accessories. Spec details may change without notice.