



WELLING & CROSSLEY

110 kVA

MODEL: ED110LC/3CAN



Powered by 

Image may vary from actual model.

THE DIESEL GENERATOR EXPERTS

Welling & Crossley is Australia's largest diesel generator and engine specialist. Australian owned and operated since 1926, Welling & Crossley is an internationally recognised Australian leader in the manufacture and supply of diesel generating sets for industrial or commercial applications. Also available is a complete range of portable, inverter or back up generators, diesel engines and fire products.

We have the expertise to provide sound advice on your power generating needs. Whether your requirements are prime (continuous) power or standby power applications, you can choose from our standard build sets, or we can tailor to suit your application requirements.

Alternator

Crossley SLG Series Alternators are single bearing, 4-pole, with a brushless, rotating field design and are self-excited with power derived from main output windings using the Automatic Voltage Regulator (AVR). Manufactured using the highest quality copper and steel with all laminations impregnated with epoxy resins, the SLG Series are of a modern design with a precision AVR that allows overloads of 10% for one hour in 12, and overloads for motor starting and short circuit protection of up to 300%. Available in either Single Phase (240V), 2-Phase (480V) or 3-Phase (415V).

The Generating Set

The complete generating set is mounted as a whole onto a heavy duty fabricated steel baseframe. Anti-vibration pads are fixed between the engine and alternator feet, and the baseframe, ensuring complete vibration isolation of the rotating assembly.

Stringent factory tests are carried out on the generating set, with a full load test completed prior to despatch. All protective devices, control functions and site load conditions are simulated. The generator and its systems are thoroughly checked prior to leaving our factory. Warranty on the genset is for 12 months or 1000 hours from date of supply (whichever occurs first) and covers against faulty workmanship, materials and design.

Engine

Lister Petter continues to set the standard in innovation, quality and reliability to meet your requirements for rated performance and efficient operation. Known worldwide for their clean, reliable and long lasting diesel engines, with a range of air cooled or radiator cooled, direct or indirect injection, naturally aspirated or turbocharged, there is a specification to suit almost any application. The engines are fitted with a highly efficient noise-reducing silencer and governed to a fixed speed of 1500rpm.

Control System

The control starting system is an Auto-Start Control Module and is fitted standard. Starting is remote or local to the machine with push Start/Stop button and includes the following:

- Alternator frequency & CAN speed sensing
- Fully configurable via the interface or PC using USB
- Generator/load power monitoring
- Accumulated power monitoring
- Generator overload protection
- Fuel and start outputs
- Engine speed protection
- Engine run-time scheduler
- Battery voltage monitoring
- Static battery charger

Can also be configured to operate with an Automatic Transfer Switch with logic.

MODEL: ED110LC/3CAN

Powered by



ENGINE SPECIFICATIONS

| | |
|----------------------------------|--------------------------|
| Engine Model | Lister Petter GWT6-2A |
| Engine Speed | 1500 rpm |
| Cylinders | 6 |
| Cubic Capacity | 5.99 L |
| Bore/Stroke | 100 x 127 mm |
| Compression Ratio | 17.5 : 1 |
| Aspiration | Turbocharged |
| Starter Voltage | 12 V |
| Flywheel (Max. Continuous Power) | 102 kW |
| Combustion Air Flow | 12.4 m ³ /min |
| Cooling Air flow | 240 m ³ /min |
| Cooling System | Water Cooled |
| Heat Rejection to Cooling System | 100 kW |
| Exhaust Gas Flow | 31.8 m ³ /min |
| Exhaust Gas Temperature | 550 °C |
| Fuel Type | Diesel |
| Fuel Tank Capacity | 260 L |
| Fuel Consumption (Continuous) | 21.8 L/h |
| Fuel Consumption (Standby) | 24 L/h |

Note: Standby reference conditions 27°C (80°F) air inlet temperature 152.4 m (500ft) ASL. All engine performance data based on the above mentioned maximum continuous ratings. Fuel consumption data at full load with diesel fuel with a specific gravity of 0.85 and conforming to BS29869:1988, Class A2.

Canopy (Standard Build)

A weather protective acoustic enclosure is fitted to protect and prolong the life of your generator. Constructed of galvanised steel sheet that is cleared and finished using a powdercoat paint finish, this acoustic canopy will reduce the noise level of the generating set to approximately 80 dB(A) at 1 metre from the machine (73 dB(A) @ 7 m).



Requires 900 mm access (width) to open doors.
Exhaust protrudes 300 mm above the canopy. Canopy Weight: 900 kg.
Dimensions: 3350 mm (L) x 1120 mm (W) x 1805 mm (H)

Specifications are subject to variation without notice.

ALTERNATOR SPECIFICATIONS

| | |
|--------------------|-----------------------------|
| Alternator Model | Crossley SLG Series |
| Electric Power | Three Phase |
| Active Power | 110 kVA at 0.8 pf (Standby) |
| Power | 88 kW |
| Electric Potential | 415 V |
| Frequency | 50 Hz |

These ratings are applicable for supplying continuous electrical power at variable load in the event of a utility power failure. No overload is permitted on these ratings.

GENERATOR SPECIFICATIONS

| | |
|------------------------|-----------------------|
| Dimensions (L x W x H) | 3350 x 1120 x 1805 mm |
| Weight | 2500 kg |

Design Features

- Heavy duty fabricated steel baseframe
- Bunded Fuel Tank (AS1940-2004 compliant)
- Battery Charger
- Control Panel with Emergency Stop button
- Prime or Standby Power

Optional Extras

- Additional Protection Alarms
- Jacket Heater
- Automatic Transfer Switch (ATS)
- Control System (remote Start/Stop) with Mains Failure option
- Weather protected acoustic canopy
- Trailer mounted
- Load Banks
- Auxiliary Fuel Tanks
- Genuine Spare Parts

Special Builds Welcome!

VICTORIA NEW SOUTH WALES QUEENSLAND SOUTH AUSTRALIA WESTERN AUSTRALIA

☎ 1300 656 276

www.wellcross.com.au